








Gas Spring End Fittings







PRODUCT CODE AND SPECIFICATIONS, WITH METRIC THREAD AND PITCH, IF APPLICABLE		
	GSKCUPPM6	
	Plastic 10 mm cup with external retaining clip, 18 mm centres.	M6 x 1.0
	GSKCUPAM6	
	Plastic 10 mm 25 degree ball cup with external retaining clip, 18 mm centres.	M6 x 1.0
	GSKCUPEM6	
	Metal 10 mm ball cup with external retaining clip, 18 mm centres.	M6 x 1.0
	GSKCUPEM8	
	Metal 10 mm ball cup with external retaining clip, 18 mm centres.	M8 x 1.25
	GSKCUPIM6	
	Metal 10 mm ball cup with internal retaining clip, 18 mm centres.	M6 x 1.0
	GSKCUPIM8	
	Metal 10 mm ball cup with internal retaining clip, 20.0 mm centres.	M8 x 1.25
	GSKCUP3M6	
	Metal 10 mm ball cup with external retaining clip, 30 mm centres.	M6 x 1.0
	GSKCUP3M8	
	Metal 10 mm ball cup with external retaining clip, 30 mm centres.	M8 x 1.25
	GSKCUPZM8	
	Powder coated 13 mm ball cup with external retaining clip, 30 mm centres.	M8 x 1.25
	GSKCUPZM10	

	Powder coated 13 mm ball cup with external retaining clip, 30 mm centres.	M10 x 1.5
	GSKCUPPM8	
	Powder coated 13 mm ball cup with external retaining clip, 20 mm centres.	M8 x 1.25
	GSKCUPM10	
	Powder coated 13 mm ball cup with external retaining clip, 20 mm centres.	M10 x 1.5
	GSSKCUPP6	
	Plastic 10 mm ball cup with external stainless steel retaining clip, 18 mm centres.	M6 x 1.0
	GSSKCUPM6	
	316 stainless steel 10 mm ball cup with external retaining clip, 18 mm centres.	M6 x 1.0
	GSSKCUPM8	
	316 stainless steel 10 mm ball cup with external retaining clip, 18 mm centres.	M8 x 1.25
	GSSKCUP13M8	
	316 stainless steel 13 mm ball cup with external retaining clip, 20 mm centres.	M8 x 1.25
	GSKBALLJOINT16M10	
	Galvanised mild steel 16 mm ball joint with 16mm ball cup, 30 mm centres and 16mm ball stud, 20mm long.	M10 x 1.5

	GSSKBALLJOINT13M8	
	304 stainless steel 13 mm ball joint with 13 mm ball cup and 13 mm ball stud.	M8 x 1.25
	GSSKBALLJOINT13M10	
	304 stainless steel 13 mm ball joint with 13 mm ball cup and 13 mm ball stud.	Cup M10 x 1.5 Stud M8 x 1.25
	GSSKBALLJOINT16M10	
	304 stainless steel 16 mm ball joint, 16 mm ball cup, 35 mm centres and 16mm stud with 20 mm long thread.	M10 x 1.5

PRODUCT CODE AND SPECIFICATIONS, WITH METRIC THREAD AND PITCH, IF APPLICABLE		
	GSKEYEE3M10	
	Metal eyelet 10 mm thick, 8 mm hole, 29 mm centres.	M10 x 1.5
	GSKEYEL8M8	
	Metal eyelet 10 mm thick, 8 mm hole, 29 mm centres.	M8 x 1.25
	GSKEYEL10M8	
	Metal eyelet, 10 mm thick, 10 mm hole, 29 mm centres.	M8 x 1.25
	GSKEYEZM6	
	Zinc eyelet 5 mm thick, 8 mm hole, 28 mm centres.	M6 x 1.0
	GSKEYEZM8	
	Zinc eyelet 5 mm thick, 8 mm hole, 30 mm centres.	M8 x 1.25
	GSKEYEP8M6	
	Metal eyelet, 5 mm thick, 8 mm hole, 18 mm centres.	M6 x 1.0
	GSKEYEP6M6	
	Metal eyelet, 5 mm thick, 6 mm hole, 18 mm centres.	M6 x 1.0
	GSKEYE6M6	
	Metal eyelet, 10 mm thick, 6 mm hole, 18 mm centres.	M6 x 1.0

	GSKEYE8M6	
	Metal eyelet, 10 mm thick, 8 mm hole, 18 mm centres.	M6 X1.0
	GSKEYE8M8	
	Metal eyelet, 10 mm thick, 8 mm hole, 18 mm centres.	M8 x 1.25
	GSKEYE10M8	
	Metal eyelet, 10 mm thick, 10 mm hole, 18 mm centres.	M8 x 1.25
	GSSKEYEM6	
	316 stainless steel eyelet, 5 mm thick, 8 mm hole, 18 mm centres.	M6 x 1.0

PRODUCT CODE AND SPECIFICATIONS, WITH METRIC THREAD AND PITCH, IF APPLICABLE		
	GSKSTUD610	
	Metal 10 mm ball stud with 20 mm long thread.	M6 x 1.0
	GSKSTUD10	
	Metal 10 mm ball stud with 12 mm long thread.	M8 x 1.25
	GSKSTUD13	
	Metal 13 mm ball stud with 15 mm long thread.	M8 x 1.25
	GSKSTD10	
	Metal 10 mm ball stud with 25 mm long thread.	M8 x 1.25
	GSKSTD13	
	Metal 13 mm ball stud with 25 mm long thread.	M8 x 1.25
	GSSKSTUD10	
	316 Stainless steel 10 mm ball stud with 12 mm long thread.	M8 x 1.25
	GSSKSTUD13	
	316 Stainless steel 13 mm ball stud with 15 mm long thread.	M8 x 1.25

PRODUCT CODE AND SPECIFICATIONS, WITH METRIC THREAD AND PITCH, IF APPLICABLE		
	GSKCLEVISM6	
	Clevis, yellow passivated with retaining clip, 6 mm hole, 25 mm centres.	M6 x 1.0
	GSKCLEVISM6L	
	Clevis, yellow passivated with retaining clip, 6 mm hole, 35 mm centres.	M6 x 1.0
	GSKCLEVISM8	
	Clevis, yellow passivated with retaining clip, 8 mm hole, 32 mm centres.	M8 x 1.25
	GSKCLEVISZ8	
	Clevis, yellow passivated with retaining clip, 8 mm hole, 40 mm centres.	M8 x 1.25
	GSKCLEVISM10	
	Clevis, yellow passivated with retaining clip, 10 mm hole, 40 mm centres.	M10 x 1.5

PRODUCT CODE AND SPECIFICATIONS, WITH METRIC THREAD AND PITCH, IF APPLICABLE		
	GSKRODMM6	
	Spherical rod end, 6 mm hole, 33 mm centres.	M6 x 1.0
	GSKRODMM8	
	Spherical rod end, 8 mm hole, 35 mm centres.	M8 x 1.25
	GSKRODM10	
	Spherical rod end, 10 mm hole, 44 mm centres.	M10 x 1.5
	GSKSTRDM6	
	Metal studded rod, 30 mm centres, including rubber boot.	M6 x 1.0
	GSKSTRDM8	
	Metal studded rod, 36 mm centres, including rubber boot.	M8 x 1.25
	GSKCR0001	
	Cable release head GSHC, 10 mm hole, 30 mm centres.	M10 x 1.0
	GSKCR0002	
	Cable release head, 8 mm hole, 30 mm centres.	M10 X 1.0